















SPECIFICATIONS

| | | |
|--|-----------------|--|
|  | GEOLOGY | Limestone |
|  | TYPE | 100% Splitface |
|  | PATTERN | 2:1 Random Ashlar |
|  | HEIGHTS | 4" - 8" |
|  | LENGTHS | 6" - 14" |
|  | DEPTHS | 3/4" to 1-1/4" |
|  | COLORS | Beige , Buff , Gray - Grey , Tan |
|  | COVERAGE | Available in thin veneer only. |
|  | WEIGHT | 13.1 lbs. per square foot. |
|  | FLATS | 10 s/f Box, 100 s/f Crate, 180 s/f Crate |
|  | CORNERS | 10 l/f Box, 100 l/f Crate |
|  | NOTES | Buff with a bluish/gray vein. |

ASTM C-97

| |
|-----------------------|
| Water Absorption % |
| Bulk Specific Gravity |

ASTM C-170

| |
|----------------------------|
| Parallel to Rift, Dry |
| Parallel to Rift, Wet |
| Perpendicular to Rift, Dry |
| Perpendicular to Rift, Wet |

ASTM C-99

| |
|-----------------------|
| Parallel to Rift, Dry |
| Parallel to Rift, Wet |

ASTM C-880

| |
|----------------------------|
| Perpendicular to Rift, Dry |
| Perpendicular to Rift, Wet |

